

INSTRUCCIONES PARA EL USO: Siga las instrucciones del fabricante de la pintura para la cantidad de diluyente de laca requerida. Recomendamos comenzar con una proporción de 4 onzas por galón. No use más de la cantidad recomendada.

¡IMPORTANTE! No extienda este producto en áreas grandes porque los peligros de incendio y riesgos para la salud aumentarán dramáticamente. No limpie o equipo de aspersión ras.

CONSEJOS ÚTILES: La mayoría de los acabados de automóviles requieren un diluyente específico para ciertos límites de temperaturas.

¡PELIGRO! EXTREMADAMENTE INFLAMABLE. LOS VAPORES PUEDEN CAUSAR UN INCENDIO O ENCENDERSE EXPLOSIVAMENTE. MANTENGASE LEJOS DEL CALOR, CHISPAS, LLAMAS Y OTRAS FUENTES DE IGNICIÓN. Extinga todas las flamas y pilotos, y apague las estufas, calentadores, motores eléctricos y cualquier otra fuente de ignición durante su uso y hasta que se hayan disipado los vapores. No fumar. Mantenerlo lejos de enchufes e interruptores eléctricos. Tenga cuidado con la electricidad estática generada por la ropa sintética y otras fuentes. **USE ÚNICAMENTE CON VENTILACIÓN ADECUADA PARA EVITAR LA ACUMULACIÓN DE VAPORES.** No use en áreas donde los vapores se puedan acumular y concentrarse tales como sótanos, cuartos de baño y áreas pequeñas y encerradas. Si se utiliza bajo techo, abra todas las ventanas y las puertas y mantenga una ventilación cruzada de aire fresco en movimiento a través del área de trabajo. Si nota un fuerte olor o si experimenta mareos – DETENGASE – la ventilación es inadecuada. Abandone el área de inmediato. **SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO USE ESTE PRODUCTO.** Una máscara para el polvo no otorga protección contra los vapores.

¡PELIGRO! NOCIVO SI SE INGIERE. VAPOR NOCIVO. IRRITANTE DE LOS OJOS. Contiene 2-propanona y éteres de glicol. Hay informes que han asociado la sobreexposición a solventes repetida y prolongada con daño neurológico y otros daños fisiológicos. El mal uso intencional de este producto al concentrar e inhalar deliberadamente los vapores puede ser dañino o mortal. No lo tragues. Evite respirar los vapores o la neblina y el contacto con la piel, los ojos o la ropa.

PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN, 1-800-222-1212, a la sala de emergencias del instrucciones. **EN CASO DE CONTACTO CON** enjuagando con agua durante al menos médica. **EN CASO DE CONTACTO CON** Lávese de inmediato con agua y

MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS.

llame a su Centro de control de intoxicaciones al hospital o al médico inmediatamente para recibir **LOS OJOS,** slos lentes de contacto y continúe 15 minutos y luego obtenga atención **LA PIEL,** puede provocar irritación. jabón.

Categoría de producto:
Diluyente de pintura
MAXIMO VOC: 25
gramos por litro



FLAMMABLE LIQUID

3

¡AVISO!
El recipiente vacío
puede contener vapores
explosivos. No corte, pinche
o suelde sobre o cerca a
este recipiente.

ATTENTION
When empty, may
contain explosive
vapors. Do not cut,
puncture or weld on or
near this container.

UN1263, PAINT RELATED MATERIAL

**Klean
Strip®**



Lacquer Thinner

CLEANS PROJECT TOOLS

Improves Flow & Leveling
Helps Resist Blushing



DANGER! EXTREMELY FLAMMABLE.
VAPORS MAY CAUSE FLASH FIRE OR IGNITE
EXPLOSIVELY. HARMFUL IF SWALLOWED.
VAPOR HARMFUL. EYE IRRITANT.
Read entire label prior to use or storage.

¡PELIGRO! EXTREMADAMENTE
INFLAMABLE. VAPORES PUEDEN
PROVOCAR COMBUSTIONES SUBITAS O
INFLAMARSE DE MANERA EXPLOSIVA.
NOCIVO SI SE INGIERE. VAPOR NOCIVO.
IRRITANTE DE LOS OJOS.
Lea toda la etiqueta antes de usar o
almacenar este producto.

FIVE GALLONS (18.925 L)



Klean-Strip® Lacquer Thinner

is a high-solvency, fast-drying thinner for lacquer and epoxy. Cleans tools and equipment after a lacquer project.

DIRECTIONS FOR USE:

Follow the coating manufacturer's instructions for the proper amount of Lacquer Thinner required. We recommend starting with 4 ounces per gallon. Do not use more than recommended.

IMPORTANT: Do not apply to floors or any other large surface areas because fire and health safety risks will increase dramatically. Do not use to clean or flush spray equipment.

HELPFUL TIPS: Most automotive finishes require a specific thinner for use within certain temperature ranges.

DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing and other sources. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small, enclosed areas. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience any dizziness – STOP – ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.** A dust mask does not provide protection against vapors.

DANGER! HARMFUL IF SWALLOWED. VAPOR HARMFUL. EYE IRRITANT. Contains 2-propanone and glycol ethers. Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Do not swallow. Avoid breathing of vapors or mist and contact with skin, eyes or clothing.

FIRST AID: IF SWALLOWED, call your Poison Control Center at 1-800-222-1222, hospital emergency room or physician immediately for instructions. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get medical attention. **IN CASE OF SKIN CONTACT,** irritation may result. Immediately wash with soap and water.

KEEP OUT OF REACH OF CHILDREN.

Product Category: Paint Thinner • **Max VOC:** 25 g/l

For assistance: Call the Barr Help Line 1-800-398-3892
Monday through Friday 8:00am to 4:30pm CT

For more ingredient information:

visit www.barringredients.com or call at 1-888-326-7743.



Product # **CML170SC**
©2019 W.M. Barr & Co., Inc.
www.kleanstrip.com
All rights reserved.

W.M. Barr & Co., Inc.
Memphis, TN 38113



J9334