



Klean-Strip® Paint Thinner diluye eficazmente la pintura a base de aceite, las manchas y el barniz. También se puede utilizar para limpiar cepillos y equipos inmediatamente después de su uso.

INSTRUCCIONES PARA EL USO: Siga las instrucciones del fabricante de la pintura para la cantidad de diluyente requerida. Recomendamos comenzar con una proporción de 4 onzas por galón. No use más de la cantidad recomendada. Agregue gradualmente y revuelva minuciosamente hasta obtener la consistencia deseada. No lo use como un diluyente para pintura látex u otros recubrimientos al agua, laca ni goma laca. Para recubrimientos recientes a base de aceite, agite la brocha o el rodillo en Diluyente de pintura hasta disolver todo residuo visible. Luego enjuague con disolvente de pintura fresco. Presione para eliminar el exceso y coloque en forma plana para secar.

IMPORTANTE: Lea todas las precauciones e instrucciones antes del uso. Solo use este producto como lo indica la etiqueta. Use gafas protectoras para sus ojos y evite el contacto prolongado con la piel.

ALMACENAMIENTO: No use ni almacene este producto cerca de fuentes de calor, llamas abiertas, zonas de hornos, llamas piloto, estufas, etc. Manténgalo en un lugar fresco y seco. Manténgalo en un sitio frío y seco lejos de la luz directa del sol a temperaturas por debajo de 120°F (48.9°C). Cierre el recipiente después de cada uso. No vuelva a usar el recipiente.

DESECHO: Si el envase presenta signos de deterioro, deseche el producto. Deseche las latas vacías y el producto remanente en las instalaciones de recolección de desechos peligrosos para uso en casa que haya en su localidad. Si no hubiera uno disponible, deséchelo de acuerdo con los reglamentos federales, estatales y locales.

¡PELIGRO! NOCIVO O FATAL SI SE INGIERE. IRRITANTE DE LOS OJOS Y LA PIEL.

Contiene destilados de petróleo. Manténgalo alejado del calor, chispas, llamas abiertas y otras fuentes de ignición. **USE SÓLO CON VENTILACIÓN ADECUADA PARA EVITAR LA CONCENTRACIÓN DE VAPORES.** No use en áreas donde se puedan acumular y concentrar los vapores tales como sótanos, baños o áreas pequeñas encerradas. Siempre que sea posible, use al aire libre en un área bien ventilada. Si va a usar el producto adentro, abra todas las ventanas y puertas y mantenga una ventilación cruzada que mueva el aire fresco a través del área de trabajo. Si nota un olor fuerte o se siente un poco mareado, con dolor de cabeza, náusea o lagrimación - PARE - la ventilación es inadecuada. Salga del área inmediatamente. **SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADO, NO USE ESTE PRODUCTO.** Una máscara contra el polvo no proporciona protección contra vapores. No para ser ingerido. Evite el contacto con los ojos o el contacto prolongado con la piel.

PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN, no induzca el vómito. Llame inmediatamente al Centro local de control de venenos al 1-800-222-1222, a la sala de emergencia de su hospital o a su médico. **EN CASO DE CONTACTO CON LOS OJOS,** lávelos inmediatamente con agua y retire cualquier lente de contacto; continúe enjuagando durante por lo menos 15 minutos y luego obtenga atención médica. **EN CASO DE CONTACTO PROLONGADO CON LA PIEL,** lave cuidadosamente con agua y jabón. Obtenga asistencia médica si persiste la irritación.

MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.

¡AVISO!

El recipiente vacío puede contener vapores explosivos. No corte, pinche o suelde sobre o cerca a este recipiente.

ATTENTION

When empty, may contain explosive vapors. Do not cut, puncture or weld on or near this container.

PAINT RELATED MATERIAL

Klean Strip®



Made With Mineral Spirits

Paint Thinner

CLEANS & THINS

Thins Oil-based Paint, Stain & Varnish
Use on Brushes & Equipment



DANGER!
HARMFUL OR FATAL IF SWALLOWED.
EYE AND SKIN IRRITANT.
COMBUSTIBLE.

Read entire label prior to use or storage.

55 GALLONS (208.175 L)

¡PELIGRO!
NOCIVO O LETAL SI SE INGIERE.
IRRITANTE DE LOS OJOS Y LA PIEL.
COMBUSTIBLE.

Lea toda la etiqueta antes de usar o almacenar este producto.



Klean-Strip® Paint Thinner effectively thins oil-based paint, stain and varnish. It can also be used to clean brushes and equipment immediately after use.

DIRECTIONS FOR USE: Follow the paint product manufacturer's instructions for the proper amount of paint thinner required. We recommend starting with 4 ounces per gallon. Do not use more than recommended. Add gradually and stir thoroughly until desired consistency is obtained. Do not use as a thinner for latex paint or other water based coatings, lacquer or shellac. To remove fresh oil-based coatings, agitate brush or roller in Paint Thinner until all visible residue is dissolved. Then rinse using fresh Paint Thinner. Press out excess and lay flat to dry.

IMPORTANT: Carefully read all directions, notes and cautions prior to use. Only use this product as directed on the label. Protect eyes with chemical splash goggles and avoid prolonged skin contact. **STORAGE:** Do not use or store this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc. Keep it in a cool, dry place, out of direct sunlight, at temperatures below 120°. Keep container closed when not in use. Do not reuse this container. **DISPOSAL:** If container shows signs of deterioration, dispose of product. Dispose of empty containers and leftover product at your local household hazardous waste collection facility. If one is not available, dispose of in accordance with federal, state and local regulations.

DANGER! HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. COMBUSTIBLE. Contains Petroleum Distillates. Keep away from heat, sparks, open flames, and other ignition sources. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORES.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.** A dust mask does not provide protection against vapors. Do not take internally. Avoid contact with eyes and prolonged contact with skin.

FIRST AID: IF SWALLOWED, do not induce vomiting. Call the Poison Control Center at 1-800-222-1222, hospital emergency room or physician immediately. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get medical attention. **IN CASE OF PROLONGED SKIN CONTACT,** wash thoroughly with soap and water. If irritation persists, get medical attention. **KEEP OUT OF REACH OF CHILDREN.**

Product Category: Paint Thinner • **Max VOC:** 3%

Not intended for sale or use in the South Coast Air Quality Management District (SCAQMD).



W.M. Barr & Co. Inc.
Memphis, TN 38113

Product # **DKPT94403CA**
©2019 W.M. Barr & Co., Inc.
www.kleanstrip.com
All rights reserved.

For more ingredient information:
visit www.barringredients.com
or call 1-888-326-7743



0 30192 94433 2

J9167