

W.M. Barr & Co., Inc., Memphis, TN 38113
For more technical information:
NSF.WMBARRPRODUCTS.COM or call 1-833-888-5319

Product Information Hotline:
1-877-GOOF-OFF • 1-877-466-3633
www.goofoffproducts.com

©2021 W.M. Barr & Co., Inc.

Reg. Nro. SA E.C.
Jos. Maranó Sales 37 Pa.
Calle 4500
Monterrey, NL, Mexico
R.F.C. 04080126941
T.L.: +5281831055
Email: info@goofoffproducts.com

GOOF OFF® Pro Strength Remover cuts through the toughest adhesives quickly. It works the first time to remove what ordinary removers can't handle. Use it to eliminate costly messes and mistakes from adhesives. It works faster and better than other removers!

FOR USE ON: Baseboards, Metals, Glass, Brick, Wood, Concrete, Grout, Fiberglass, Hand Tools and most Automotive Surfaces. Also safe on fully cured varnished and oil-base painted surfaces. Also works on Crayon, Adhesives & Glue, Stickers & Decals, Caulk, Dried Latex Paint, Tar & Road Grime*, Bugs & Tree Sap*.

DIRECTIONS: Always use safety goggles. People with sensitive skin should use solvent resistant gloves. Apply to a cloth, then blot or rub lightly. You may need to rework some surfaces to renew gloss. **IMPORTANT!** Always test on an inconspicuous area first, as every hard surface is different. Damage many plastics, worn vinyl floors, vinyl siding, some automotive paints, and some carpets.

DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing and other sources. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small, enclosed areas. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience any dizziness - STOP - Ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.** A dust mask does not provide protection against vapors.

DANGER! HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL, EYE IRRITANT. Contains Acetone and Xylene. Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Avoid contact with eyes and contact with skin. Avoid breathing of vapors or mist and contact with skin, eyes and clothing. Do not swallow.

WARNING: This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

FIRST AID: IF SWALLOWED, do not induce vomiting. Call the Poison Control Center (1-800-222-1222), hospital emergency room or physician immediately for instructions. IN CASE OF EYE CONTACT, immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes. If irritation persists, get medical attention. IN CASE OF SKIN CONTACT, immediately wash with soap and water. If irritation persists, get medical attention. KEEP OUT OF REACH OF CHILDREN.



Product Category:
General Purpose
Adhesive Remover
Max VOC: 20%
*Regulations only allow use on painted automobile surfaces.

PELIGRO! EXTRAMADAMENTE INFLAMABLE. VAPORES PUEDE CAUSAR UN INCENDIO O EXPLOSIÓN. MANTÉNGASE FUERA DEL CALOR, CÁPSULAS, LLAMAS Y TODAS LAS DEMÁS FUENTES DE LLAMAS. Mantenga alejado de estufas, lámparas y luces, y luces de pie, y cualquier otra fuente de calor. No fume ni encienda cigarrillos ni cigarros cerca de este producto. NO LO USE EN EL INTERIOR ATRÁS TORNOS NI VENTILADORES. La ventilación es indispensable. Salida de aire y portas y puertas para ventilación en el lado de trabajo. Si nota un dolor fuerte o experimenta náuseas - DETÉNGASE. La ventilación es indispensable. Salida de aire y portas y puertas para ventilación en el lado de trabajo. Una máscara antigás con una protección contra los vapores. **PELIGRO! OCINO Y MORTAL SI SE INGERE. VAPOR OCINO. RITMO LOS OJOS. Contiene acetona y xileno. Estudios efectuados asocian la sobre exposición repetida a las superficies con daños neurológicos y fisiológicos. El uso de este producto puede causar daños a los ojos y la piel y la boca. No lo ingerir.**

ADVERTENCIA: Este producto puede exporle a agentes químicos, incluido el etilbenzeno, que en el estado de California se considera cancerígeno, y al metanol, que el estado de California



PRO STRENGTH REMOVER



DRIED LATEX PAINT

REMOVES THE
TOUGHEST STUFF™
ULTRA FAST - ULTRA STRONG

DANGER! EXTREMELY FLAMMABLE.
VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY.
VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. EYE IRRITANT.
Read entire label prior to use or storage.

:Peligro! EXTRAMADAMENTE INFLAMABLE.
LOS VAPORES PUEDEN CAUSAR UN INCENDIO REPENTINO O EXPLOTAR.
VAPOR OCINO. OCINO Y MORTAL SI SE INGERE. IRITRA LOS OJOS.
Lea la etiqueta completa antes de su uso o almacenamiento.

6 FL OZ (177 mL)

PRIMEROS AUXILIOS SI SE INGERE, no inducir el vómito. Llene inmediatamente a un centro de control toxicológico de su lugar o a su médico para solicitar instrucciones. EN CASO DE CONTACTO CON LOS OJOS, lavarlos inmediatamente con agua y efter, colgarles lentes de contacto, cortar el cabello cerca del ojo y sacar la joyería. Si la irritación persiste, obtegn atención médica. EN CASO DE CONTACTO CON LA PIEL, lave inmediatamente con agua y jabón. Si la irritación persiste, obtegn atención médica. NO LO USE AL ALTAZAR DE LOS HIJOS.

*En aplicaciones solo permitido el uso en superficies pintadas de automóviles.

Categoría del producto: Remoción de adhesivos. % uso general: 20%.