

PROFESSIONAL STRENGTH

JASCO



SEMI-PASTE

PREMIUM PAINT & EPOXY REMOVER



NON-METHYLENE CHLORIDE FORMULA

STRIPS MULTIPLE LAYERS

Use on Wood, Metal, Concrete & Masonry

Brushable - Clings to Surfaces

Water-Rinsable



DANGER! EXTREMELY FLAMMABLE.
VAPORS MAY CAUSE FLASH FIRE OR
IGNITE EXPLOSIVELY. HARMFUL OR
FATAL IF SWALLOWED. CAUSES BURNS.
VAPOR HARMFUL.

Read entire label prior to use or storage.

1 GALLON (3.785 L)

¡PELIGRO! EXTREMADAMENTE
INFLAMABLE. LOS VAPORES PUEDEN
CAUSAR UN INCENDIO O INCENDIO
EXPLOSIVO, NOCIVO O LETAL SI SE
INGIERE. CAUSA QUEMADURAS.
VAPOR NOCIVO. Lea toda la etiqueta
antes de usar o almacenar este producto.

PATENT PENDING J9129T

DIRECTIONS FOR USE: 1. **Shake well.** 2. Pour into a metal container and apply a thick coat with a paint brush to a small area (up to 3 ft. x 3 ft.). Brush in one direction only. Leave the area and let the stripper do the work. 3. After 15 minutes, test scrape a small area to see if finish is ready for removal. Remove loosened finish by gently scraping in direction of wood grain with a plastic stripping tool. A toothbrush, toothpick or stripping brush will help remove old finish buried in recesses. Multiple coats or stubborn finishes may require repeat application. 4. Use a clean abrasive pad dipped in after wash or mineral spirits to loosen remaining finish and remove any residue. Surface should be completely clean and dry before refinishing.

IMPORTANT: Do not apply to floors or any other large surface areas because fire and health safety risks will increase dramatically. Always wear chemical-splash goggles and chemical-resistant gloves when handling this product. A dust mask does not provide protection against vapors. Dispose of product within 3 months of opening.

DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing and other sources. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small, enclosed areas. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience dizziness – STOP – ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.**

DANGER! HARMFUL OR FATAL IF SWALLOWED. CAUSES BURNS. VAPOR HARMFUL. Contains Acetone and Xylene. Reports have associated repeated and prolonged over-exposure to solvents with neurological and other physiological damage. The risk to your health depends on the level and duration of exposure. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Avoid breathing vapors or mist and contact with skin, eyes, and clothing. Do not swallow.

⚠️ WARNING: This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

FIRST AID: INHALATION: First move person to fresh air. If not breathing, give artificial respiration. Call 911, or Poison Control Center (1-800-222-1222), or emergency room, as soon as possible. **EYE EXPOSURE:** Immediately flush affected eye(s) with water. Call 911, or Poison Control Center, or emergency room, as soon as possible. **SKIN EXPOSURE:** Immediately wash skin with soap and water. Avoid spreading material on unaffected skin. Remove contaminated clothing and shoes, and thoroughly clean before reuse. Contact medical professional for advice. **IF SWALLOWED:** IMMEDIATELY call 911, or Poison Control Center, or emergency room, as soon as possible. **DO NOT INDUCE VOMITING** unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

KEEP OUT OF REACH OF CHILDREN. DO NOT USE TO STRIP BATHTUBS.

Product Category: Paint Remover • Max VOC: 50%

¡PELIGRO! EXTREMADAMENTE INFLAMABLE. LOS VAPORES PUEDEN CAUSAR UN INCENDIO O INCENDIO EXPLOSIVO. MANTENGASE FUERA DEL CALOR, CHISPAS, LLAMAS Y TODAS LAS DEMAS FUENTES DE IGNICION. Apague todas las llamas y luces piloto, y apague todas las estufas, calentadores, motores eléctricos y todas las otras fuentes de ignición durante el uso y hasta que todos los vapores se hayan ido. No fume. Mantener alejado de enchufes eléctricos e interruptores. Tenga cuidado con la electricidad estática generada por la ropa sintética y otras fuentes. **ÚSELO ÚNICAMENTE CON VENTILACIÓN ADECUADA PARA EVITAR LA EXISTENCIA DE VAPORES.** No lo use en áreas donde los vapores se puedan acumular y concentrar, como sótanos, baños y áreas pequeñas y cerradas. Si lo usa en el interior, abra todas las ventanas y puertas y mantenga una ventilación cruzada de aire fresco en movimiento en el área de trabajo. Si se nota un fuerte olor o si experimenta mareos – DETENGASE – la ventilación es inadecuada. Salga del área inmediatamente. **SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO USE ESTE PRODUCTO.**

¡PELIGRO! NOCIVO O LETAL SI SE INGIERE. CAUSA QUEMADURAS. VAPOR NOCIVO. Contiene acetona y xileno. Los informes han asociado la sobreexposición repetida y prolongada a solventes con daños neurológicos y otros daños fisiológicos. El riesgo para su salud depende del nivel y la duración de la exposición. El uso indebido intencional de este producto al concentrar e inhalar vapores deliberadamente puede ser dañino o fatal. Evite respirar los vapores o la niebla y el contacto con la piel, los ojos y la ropa. No debe ingerirse.

⚠️ ADVERTENCIA: Este producto puede exponerlo a sustancias químicas como el etilbenceno, que el estado de California sabe que causa cáncer. Para obtener más información, vaya a www.P65Warnings.ca.gov.

PRIMEROS AUXILIOS: INHALACIÓN: Primero mueva a la persona a un lugar con aire fresco. Si no respira, administre respiración artificial. Llame al 911, o al centro de control de envenenamiento (1-800-222-1222), o a la sala de emergencias, tan pronto como sea posible. **EXPOSICIÓN DE LOS OJOS:** Inmediatamente enjuague los ojos afectados con agua. Llame al 911, o al centro de control de envenenamiento, o a la sala de emergencias, tan pronto como sea posible. **EXPOSICIÓN DE LA PIEL:** Lave la piel inmediatamente con agua y jabón. Evite extender el material sobre la piel no afectada. Quite la ropa y los zapatos contaminados y lávelos minuciosamente antes de volver a usarlos. Póngase en contacto con un profesional médico para obtener consejos. **EN CASO DE INGESTIÓN: INMEDIATAMENTE** llame al 911, al centro de control de envenenamiento o a la sala de emergencias, tan pronto como sea posible. **NO INDUCIR EL VOMITO** a menos que así lo indique el personal médico. Nunca le dé nada por la boca a una persona inconsciente. **MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

NO LO UTILICE PARA DESMONTAR BAÑERAS. IMPORTADOR SERVICIOS HOME DEPOT, S. de R.L. de C.V. RICARDO MARGAIN 605 SANTA ENGRACIA, SAN PEDRO GARZA GARCIA, Nuevo León, C.P. 66267. MEXICO R.F.C. SHD-940509-158 TEL 81 55 70 00

Categoría de producto: Removedor de Pintura
COV Máx.: 50%

Latex	* Strips 5 layers in 15 minutes
Oil/Alkyd	Strips 5 layers in 45 minutes

GJPR500SC / J9130T



0 26452 01500 3

