

GOOFOFF

Works The 1st Time!

works in
**15
MIN***

GRAFFITI REMOVER



DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. HARMFUL OR FATAL IF SWALLOWED. CAUSES BURNS. VAPOR HARMFUL. CONTENTS UNDER PRESSURE.

Read entire label prior to use or storage.

¡PELIGRO! EXTREMADAMENTE INFLAMABLE. LOS VAPORES PUEDEN CAUSAR UN INCENDIO O INCENDIO EXPLOSIVO. DAÑINO O LETAL SI LO INGERE. CAUSA QUEMADURAS. VAPOR NOCIVO. CONTENIDO BAJO PRESIÓN.

Lea toda la etiqueta antes de usar o almacenar este producto.

16 OZ (453 g)

Removes most types of graffiti - spray paint, latex paint. Virtually eliminates the need to seal graffiti marks. Gelled formula will cling to most surfaces.

FOR USE ON: Stone, concrete, brick, metals, glass, fiberglass, wood, fully cured varnished and oil-based painted surfaces. May damage some plastics. Do not use on plastic.

PRECAUTIONS: Always test on an inconspicuous area first (extremely important on auto finishes and vinyl). May dull or damage some surfaces. Sometimes the color is not solid throughout some vinyls and can be easily removed.

NOTE: Re-painted surfaces may dry with a visible gloss difference between affected areas. *Time to work may vary depending on age and type of paint.

DIRECTIONS: Shake well. First, attempt to remove marks by applying product to cloth, then rubbing. If this fails, lightly apply product directly to surface. If no damage is observed, a natural fiber scrub brush may be used to gently loosen marks. Blot, rinse or powerwash residue.

DISPOSAL: Dispose of in accordance with local, state and federal regulations.

DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing and other sources. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small, enclosed areas. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience dizziness - STOP - ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.**

DANGER! HARMFUL OR FATAL IF SWALLOWED. CAUSES BURNS. VAPOR HARMFUL. Contains Acetone, Xylene and aerosol propellant. Reports have associated repeated and prolonged over-exposure to solvents with neurological and other physiological damage. The risk to your health depends on the level and duration of exposure. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Avoid breathing vapors or mist and contact with skin, eyes, and clothing. Do not swallow.

DANGER! CONTENTS UNDER PRESSURE. Do not puncture or incinerate. Do not store at or expose to temperatures above 120°F. Exposure to heat or prolonged exposure to sun can cause bursting. **IMPORTANT:** Do not apply to floors or any other large surface areas because fire and health safety risks will increase dramatically. Always wear chemical-splash goggles and chemical-resistant gloves when handling this product. A dust mask does not provide protection against vapors.

⚠ WARNING: This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

FIRST AID: IF SWALLOWED, do not induce vomiting. Immediately call the Poison Control Center (1-800-222-1222), hospital emergency room or physician for instructions. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get immediate medical attention. **IN CASE OF SKIN CONTACT,** immediately wash with soap and water. If irritation persists, get medical attention.

KEEP OUT OF REACH OF CHILDREN.

Product Category: Graffiti Remover
MAX VOC: 50%

Product Information Hotline:

☎ 1-877-GOOFOFF
1-877-466-3633

www.gooffproducts.com

For more ingredient information:
visit www.barringredients.com
or call 1-833-880-5319

PARA USO EN: Piedra, concreto, ladrillo, metales, vidrio, fibra de vidrio, madera, superficies barnizadas totalmente curadas o pintadas con pintura a base de aceite. Daña muchos tipos de plástico. No lo use en plástico.

PRECAUCIONES: Siempre pruébelo primero en un área poco visible primero (extremadamente importante en acabados automotrices y vinilo). Puede deslustrar o dañar algunas superficies. A veces el color no es uniforme sobre algunos tipos de vinilo y puede retirarse fácilmente.

NOTA: Las superficies repintadas se pueden secar con una diferencia visible en el brillo entre las áreas afectadas.

*El tiempo de trabajo puede variar según la edad y el tipo de pintura.

INSTRUCCIONES: Agite bien. Trate primero de retirar las marcas aplicando el producto con un paño y luego frotando. Si esto no resulta, aplique ligeramente el producto en forma directa a la superficie. Si no se observa ningún daño puede utilizar un cepillo de fibras naturales para raspar aflojar suavemente las marcas. Absorba, enjuague o lave a presión para retirar los residuos.

DISPOSICIÓN: Deseche de acuerdo con las regulaciones locales, estatales y federales.

¡PELIGRO! EXTREMADAMENTE INFLAMABLE. LOS VAPORES PUEDEN CAUSAR UN INCENDIO O INCENDIO EXPLOSIVO. MANTENGASE FUERA DEL CALOR, CHISPAS, LLAMAS Y TODAS LAS DEMÁS FUENTES DE IGNICIÓN. Apague todas las llamas y luces piloto, y apague todas las estufas, calentadores, motores eléctricos y todas las otras fuentes de ignición durante el uso y hasta que todos los vapores se hayan ido. No fume. Mantener alejado de enchufes eléctricos e interruptores. Tenga cuidado con la electricidad estática generada por la ropa sintética y otras fuentes. **USEDO ÚNICAMENTE CON VENTILACIÓN ADECUADA PARA EVITAR LA EXISTENCIA DE VAPORES.** No lo use en áreas donde los vapores se puedan acumular y concentrar, como sótanos, baños y áreas pequeñas y cerradas. Si lo usa en el interior, abra todas las ventanas y puertas y mantenga una ventilación cruzada de aire fresco en movimiento en el área de trabajo. Si se nota un fuerte olor o si experimenta mareos - DETENGASE - la ventilación es inadecuada. Salga del área inmediatamente. **SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO USE ESTE PRODUCTO.**

¡PELIGRO! DAÑINO O LETAL SI LO INGERE. CAUSA QUEMADURAS. VAPOR NOCIVO. Contiene propellente de acetona, xileno y aerosol. Los informes han asociado la sobreexposición repetida y prolongada a solventes con daños neurológicos y otros daños fisiológicos. El riesgo para su salud depende del nivel y la duración de la exposición. El uso indebido intencional de este producto al concentrar e inhalar vapores deliberadamente puede ser dañino o fatal. Evite respirar los vapores o la niebla y el contacto con la piel, los ojos y la ropa. No debe ingerirse.

¡PELIGRO! CONTENIDO BAJO PRESIÓN. No pinche ni incinere. No almacenar ni exponer a temperaturas superiores a 120°F. La exposición al calor o la exposición prolongada al sol pueden causar estallidos. **IMPORTANTE:** No aplique en pisos ni en otras superficies grandes porque los riesgos de incendio y explosión aumentarán drásticamente. Siempre use gafas de protección contra salpicaduras de sustancias químicas y guantes resistentes a los productos químicos cuando maneje este producto. Una máscara antipolvo no brinda protección contra vapores.

⚠ ADVERTENCIA: Este producto puede exponerlo a productos químicos, incluido el etilbenceno, que el estado de California sabe que causa cáncer. Para obtener más información, vaya a www.P65Warnings.ca.gov.

PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN, no induzca el vómito. Llame inmediatamente al Centro de Control de Envenenamientos (1-800-222-1222), a la sala de emergencias del hospital o al médico para recibir instrucciones. **EN CASO DE CONTACTO CON LOS OJOS,** lave inmediatamente con agua, retire cualquier lente de contacto, continúe enjuagando con agua durante al menos 15 minutos, luego obtenga atención médica inmediata. **EN CASO DE CONTACTO CON LA PIEL,** lave inmediatamente con agua y jabón. Si la irritación persiste, obtenga atención médica.

MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS.
Categoría de producto: Removedor de Pintura
MAX VOC: 50%

barr
BRANDS

Sold by: Barr Brands, ©2026
Memphis, TN 38113

FG673 / C1412

