

Formulated to meet low VOC limits; see warnings on label.
Formulado para cumplir con los límites bajos de VOC;
ver advertencias en la etiqueta.

PROFESSIONAL STRENGTH



PAIN THINNER

CLEANS & THINS

Thins Oil-based Paint, Stain & Varnish
Use on Brushes & Equipment

DANGER! EXTREMELY
FLAMMABLE. VAPORS MAY
CAUSE FLASH FIRE OR IGNITE
EXPLOSIVELY. VAPOR HARMFUL.
EYE IRRITANT.

Read entire label prior to use or storage.

¡PELIGRO! EXTREMADAMENTE
INFLAMABLE. LOS VAPORES PUEDEN
CAUSAR UN INCENDIO ESPONTANEO O
INCENDIARSE EXPLOSIVAMENTE. VAPOR
NOCIVO. IRRITANTE DE LOS OJOS.

Lea toda la etiqueta antes de usar o almacenar
este producto.

1 GALLON (3.785 L)

J9287

Jasco® Paint Thinner is a strong, fast-acting solvent that is a thinner for oil-based paint, stains and varnish.

DIRECTIONS FOR USE: Follow product manufacturer's instructions for adding paint thinner. Use sparingly as paint thinner will cause coatings to become flammable.

INSTRUCCIONES PARA EL USO: Siga las instrucciones del fabricante del producto para agregar adelgazante para pintura. Use con moderación ya que el adelgazante para pintura causará que los recubrimientos se tornen inflamables.

IMPORTANT: Do not spread this product over surface areas greater than 1 sq. foot because fire and health safety risks will increase dramatically. Do not use to clean or flush spray equipment. Paint Thinner may soften or damage plastics, synthetics, and many other finishes.

DANGER! USE WITH CAUTION: THIS PRODUCT IS EXTREMELY FLAMMABLE. THINNED COATINGS MAY BECOME EXTREMELY FLAMMABLE. FOLLOW ALL CAUTIONS BELOW WHEN USING THINNED COATINGS. DO NOT USE TO CLEAN OR FLUSH SPRAY EQUIPMENT.

DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing and other sources. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small, enclosed areas. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience any dizziness – STOP – ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.** A dust mask does not provide protection against vapors.

DANGER! VAPOR HARMFUL. EYE IRRITANT. Contains Acetone, Petroleum Distillates and Parachlorobenzotrifluoride. Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Do not swallow. Avoid breathing of vapors or mist and contact with skin, eyes or clothing.

⚠ WARNING: This product can expose you to chemicals including p-Chloro- α,α,α -Trifluorotoluene (PCBTF), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

FIRST AID: IF SWALLOWED, call your Poison Control Center at 1-800-222-1222, hospital emergency room or physician immediately for instructions. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get medical attention. **IN CASE OF SKIN CONTACT,** irritation may result. Immediately wash with soap and water.

KEEP OUT OF REACH OF CHILDREN.

Product Category: Paint Thinner • **Max VOC:** 25 g/l

For assistance: Call the Barr Help Line 1-800-398-3892 Monday through Friday 8:00am to 4:30pm CT

IMPORTANTE: No extienda este producto sobre áreas de superficie de más de 1 pie cuadrado porque los riesgos de seguridad contra incendios y para la salud aumentarán dramáticamente. No lo use para limpiar o enjuagar equipos de pulverización. El Diluyente de pintura puede suavizar o dañar plásticos, sintéticos y muchos otros acabados.

PELIGRO! USE CON PRECAUCIÓN: ESTE PRODUCTO ES EXTREMADAMENTE INFLAMABLE. LOS RECUBRIMIENTOS ADELGAZADOS PUEDEN TORNARSE EXTREMADAMENTE INFLAMABLES. SIGA TODAS LAS PRECAUCIONES A CONTINUACIÓN AL USAR RECUBRIMIENTOS ADELGAZADOS. NO USE PARA LIMPIAR EQUIPO NI CON PISTOLAS PULVERIZADORAS.

¡PELIGRO! EXTREMADAMENTE INFLAMABLE. LOS VAPORES PUEDEN CAUSAR UN INCENDIO O ENCENDERSE EXPLOSIVAMENTE. MANTENGASE LEJOS DEL CALOR, CHISPAS, LLAMAS Y OTRAS FUENTES DE IGNICIÓN. Extinga todas las flamas y pilotos, y apague las estufas, calentadores, motores eléctricos y cualquier otra fuente de ignición durante su uso y hasta que se hayan disipado los vapores. No fumar. Mantenerlo lejos de enchufes e interruptores eléctricos. Tenga cuidado con la electricidad estática generada por la ropa sintética y otras fuentes. **USE ÚNICAMENTE CON VENTILACIÓN ADECUADA PARA EVITAR LA ACUMULACIÓN DE VAPORES.** No use en áreas donde los vapores se puedan acumular y concentrarse tales como sótanos, cuartos de baño y áreas pequeñas y encerradas. Si se utiliza bajo techo, abra todas las ventanas y las puertas y mantenga una ventilación cruzada de aire fresco en movimiento a través del área de trabajo. Si nota un fuerte olor o si experimenta mareos – DETENGASE – la ventilación es inadecuada. Abandone el área de inmediato. **SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO USE ESTE PRODUCTO.**

Una máscara para el polvo no otorga protección contra los vapores. **¡PELIGRO! NOCIVO SI SE INGIERE. VAPOR DAÑINO. IRRITA LOS OJOS.** Contiene Acetona, Destilados de Petróleo y Parachlorobenzotrifluoruro. Hay informes que han asociado a la sobreexposición a solventes repetida y prolongada con daño neurológico y otros daños fisiológicos. El mal uso intencional de este producto al concentrar e inhalar deliberadamente los vapores puede ser dañino o mortal. No lo tragues. Evite respirar los vapores o la neblina y el contacto con la piel, los ojos o la ropa.

⚠ ADVERTENCIA: Este producto puede exponerlo a químicos que incluyen p-Cloro- α,α,α -Trifluorotoluene (PCBTF), que el Estado de California sabe que causan cáncer. Para obtener más información, visite www.P65Warnings.ca.gov.

PRIMEROS AUXILIOS: SI SE TRAGA, para recibir instrucciones llame de inmediato a su Centro de Control de Envenenamientos al 1-800-222-1222, sala de emergencia del hospital o médico. **EN CASO DE CONTACTO CON LOS OJOS,** enjuague de inmediato con agua, quítese los lentes de contacto y continúe enjuagando con agua durante al menos 15 minutos y luego obtenga atención médica. **EN CASO DE CONTACTO CON LA PIEL,** puede provocar irritación. Lávese de inmediato con agua y jabón.

MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS.

Categoría de producto: Diluyente de pintura • **COV-Max:** 25 g/l

©2020 W.M. Barr & Co., Inc. • www.jasco-help.com

W.M. Barr & Co., Inc., Memphis, TN 38113

GUPT150PSC / J9608



For more ingredient information: visit www.barringredients.com or call 1-833-880-5319