

Klean Strip Painter's Solvent for SCAQMD

Revision: 10/03/2019

Supersedes Revision: 08/19/2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Klean Strip Painter's Solvent for SCAQMD

Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113

Phone Number: (901)775-0100

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346

Information: W.M. Barr Customer Service (800)398-3892

Intended Use: Speciality paint thinning and cleaning painting tools & equipment.

Product Code: QKSP95005SC, GKSP95000SC

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2

Serious Eye Damage/Eye Irritation, Category 2

Specific Target Organ Toxicity (single exposure), Category 3

**GHS Signal Word:** Danger

GHS Hazard Phrases: Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause respiratory irritation.

GHS Precautionary Phrases: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing gas/mist/vapors/spray.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Keep cool.

GHS Response Phrases: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTER or doctor/physician if you feel unwell.
If eye irritation persists, get medical advice/attention.

GHS Storage and Disposal Phrases: Store container tightly closed in well-ventilated place.
Store locked up.
Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Klean Strip Painter's Solvent for SCAQMD

Revision: 10/03/2019

Supersedes Revision: 08/19/2019

**Potential Health Effects
(Acute and Chronic):**

This product has not been tested as a whole to determine health effects. The health effects listed below are associated with the individual ingredients listed in Section 3.

EYES: Irritating to the eyes. Causes itching, burning, redness and tearing. May cause corneal injury.

SKIN: May cause skin irritation. Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering. Skin absorption can transport other toxins into the body.

INHALATION: Causes respiratory tract irritation. Vapors may be irritating to eyes, nose, throat, and lungs. Inhalation of high vapor concentrations can cause central nervous system (CNS) depression and narcosis. High vapor concentrations can cause headaches, dizziness, drowsiness, and nausea, and may lead to unconsciousness.

INGESTION: Aspiration hazard if swallowed - can enter lungs and cause damage. May cause irritation of the gastrointestinal tract. May cause systemic poisoning with symptoms paralleling those of inhalation.

CHRONIC OVEREXPOSURE EFFECTS: Causes headache, drowsiness or other effects to the central nervous system. Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering. May cause target organ or system damage to the following: respiratory system, nervous system, kidney, blood system, liver. Prolonged or repeated breathing or swallowing of large amounts may cause liver and kidney damage based on reported animal studies.

TARGET ORGANS: Eyes, Skin, Respiratory system Central nervous system, Heart

PRIMARY ROUTES OF ENTRY: Inhalation, Skin, Ingestion

Medical Conditions Generally Aggravated By Exposure: Skin disorders, Eye disorders, Cardiac irregularities, Respiratory disorders, Asthma

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
67-64-1	Acetone {2-Propanone}	80.0 -100.0 %
79-20-9	Methyl acetate (Methyl ester of acetic acid)	10.0 -30.0 %
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	1.0 -5.0 %

Additional Chemical Information

Specific percentage of composition is being withheld as a trade secret.

Klean Strip Painter's Solvent for SCAQMD

Revision: 10/03/2019

Supersedes Revision: 08/19/2019

4. FIRST AID MEASURES

Emergency and First Aid Procedures:
Skin:

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down.

5. FIRE FIGHTING MEASURES

Flash Pt:	NFPA Class IB 0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: N.D. UEL: N.D.
Autoignition Pt:	N.D.
Suitable Extinguishing Media:	Dry chemical, CO2, water spray or alcohol-resistant foam.
Unsuitable Extinguishing Media:	Solid streams of water may be ineffective and spread material.
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
Flammable Properties and Hazards:	No data available.
Hazardous Combustion Products:	Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:

Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Klean Strip Painter's Solvent for SCAQMD

Revision: 10/03/2019

Supersedes Revision: 08/19/2019

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling: Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

If the work area is not well ventilated, do not use this product.

Precautions To Be Taken in Storing: Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
67-64-1	Acetone {2-Propanone}	ACGIH TLV	TLV: 500 ppm STEL: 750 ppm	
		OSHA PELs	PEL: 1000 ppm	
79-20-9	Methyl acetate (Methyl ester of acetic acid)	ACGIH TLV	TLV: 200 ppm STEL: 250 ppm	
		OSHA PELs	PEL: 200 ppm	
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	ACGIH TLV	TLV: 200 mg/m ³	

Respiratory Equipment (Specify Type): For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

Eye Protection: Safety glasses should be worn during normal handling of this material.

Where contact with the eyes or face is likely, a faceshield or chemical splash goggles should be worn to prevent eye contact.

Protective Gloves: Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not

SAFETY DATA SHEET

Klean Strip Painter's Solvent for SCAQMD

Revision: 10/03/2019

Supersedes Revision: 08/19/2019

Other Protective Clothing:	reused. Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.
Engineering Controls (Ventilation etc.):	Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air. If the work area is not well ventilated, do not use this product.
Work/Hygienic/Maintenance Practices:	Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom. Do not eat, drink, or smoke in the work area. Discard any clothing or other protective equipment that cannot be decontaminated. Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	<input type="checkbox"/> Gas <input checked="" type="checkbox"/> Liquid <input type="checkbox"/> Solid
Appearance and Odor:	Water white liquid free and clear. Odor threshold not determined.
pH:	N.D.
Melting Point:	N.D.
Boiling Point:	N.D.
Flash Pt:	0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Evaporation Rate:	> 1
Flammability (solid, gas):	No data available.
Explosive Limits:	LEL: N.D. UEL: N.D.
Vapor Pressure (vs. Air or mm Hg):	N.D.
Vapor Density (vs. Air = 1):	> 1
Specific Gravity (Water = 1):	0.7980 - 0.8180
Density:	6.723 LB/GL
Solubility in Water:	N.D.

SAFETY DATA SHEET

Klean Strip Painter's Solvent for SCAQMD

Revision: 10/03/2019

Supersedes Revision: 08/19/2019

Octanol/Water Partition Coefficient:	ND
Percent Volatile:	100.0 % by weight.
VOC / Volume:	3.0000 % WT
Autoignition Pt:	N.D.
Decomposition Temperature:	N.D.
Viscosity:	N.D.
Additional Physical Information	ND = Not Determined.

10. STABILITY AND REACTIVITY

Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	No data available.
Incompatibility - Materials To Avoid:	Oxidizers, acids, aldehydes, alkalis, amines, ammonia, reducing agents, chlorine compounds, chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide, thioglycol.
Hazardous Decomposition or Byproducts:	May form carbon monoxide, carbon dioxide, acetic acid, methanol, and various hydrocarbons.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	No data available.

11. TOXICOLOGICAL INFORMATION

Toxicological Information:	This product has not been tested as a whole. Refer to section 2 for acute and chronic effects. CAS# 67-64-1: Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe. Result: Behavioral: Change in motor activity (specific assay). Behavioral: Alteration of classical conditioning. - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946
Carcinogenicity/Other Information:	ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
79-20-9	Methyl acetate (Methyl ester of acetic acid)	n.a.	n.a.	n.a.	n.a.
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	n.a.	n.a.	A4	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information:	This product has not been tested as a whole.
--	--

Klean Strip Painter's Solvent for SCAQMD

Revision: 10/03/2019

Supersedes Revision: 08/19/2019

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with local, state, and federal laws.

Do not place material in general trash.

Do not allow material to enter bodies of water or sewers.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint related material

DOT Hazard Class: 3 FLAMMABLE LIQUID

UN/NA Number: UN1263 **Packing Group:** II



Additional Transport Information:

The shipper / supplier may be able to apply one of the following exceptions if allowed under 49 CFR Regulations: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49 CFR Hazmat Regulations. Please consult 49 CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
79-20-9	Methyl acetate (Methyl ester of acetic acid}	No	No	No
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
67-64-1	Acetone {2-Propanone}	TSCA: Inventory
79-20-9	Methyl acetate (Methyl ester of acetic acid}	TSCA: Inventory, 8A PAIR
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	TSCA: Inventory

Regulatory Information: This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

Regulatory Information Statement: All components of this material are listed on the TSCA Inventory or are exempt.

SAFETY DATA SHEET

Klean Strip Painter's Solvent for SCAQMD

Revision: 10/03/2019

Supersedes Revision: 08/19/2019

16. OTHER INFORMATION

Revision Date: 10/03/2019
Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About This Product: No data available.

This Product:

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.