

## Jasco Green Safer Paint Thinner for CARB

Revision: 10/02/2019

Supersedes Revision: 09/16/2019

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	Jasco Green Safer Paint Thinner for CARB	
<b>Company Name:</b>	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	<b>Phone Number:</b> (901)775-0100
<b>Web site address:</b>	www.wmbarr.com	
<b>Emergency Contact:</b>	3E 24 Hour Emergency Contact	(800)451-8346
<b>Information:</b>	W.M. Barr Customer Service	(800)398-3892
<b>Intended Use:</b>	Cleaner and degreaser	
<b>Product Code:</b>	QJGPT454, GJGPT450	

## 2. HAZARDS IDENTIFICATION

## Aspiration Toxicity, Category 1



<b>GHS Signal Word:</b>	<b>Danger</b>
<b>GHS Hazard Phrases:</b>	May be fatal if swallowed and enters airways.
<b>GHS Precautionary Phrases:</b>	No phrases apply.
<b>GHS Response Phrases:</b>	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
<b>GHS Storage and Disposal Phrases:</b>	Store locked up. Dispose of contents/container according to local, state and federal regulations.
<b>OSHA Regulatory Status:</b>	This material is classified as hazardous under OSHA regulations.
<b>Potential Health Effects (Acute and Chronic):</b>	This product has not been tested as a whole to determine health effects. The health effects listed below are associated with the individual ingredients listed in Section 3.
	<b>EYES:</b> May cause eye irritation.
	<b>SKIN:</b> Prolonged skin contact may cause skin irritation and/or dermatitis.
	<b>INHALATION:</b> Prolonged exposure through inhalation may be harmful.
	<b>INGESTION:</b> Harmful if swallowed.
	<b>CHRONIC OVEREXPOSURE EFFECTS:</b> None known.
	<b>TARGET ORGANS:</b> skin, eyes
	<b>PRIMARY ROUTES OF ENTRY:</b> skin

## Jasco Green Safer Paint Thinner for CARB

Revision: 10/02/2019

Supersedes Revision: 09/16/2019

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	15.0 -40.0 %

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

### 4. FIRST AID MEASURES

<b>Emergency and First Aid Procedures:</b>	<p><b>Skin:</b> Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.</p> <p><b>Eyes:</b> Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.</p> <p><b>Inhalation:</b> Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.</p> <p><b>Ingestion:</b> If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down.</p>
<b>Note to Physician:</b>	Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

<b>Flash Pt:</b>	N.D.
<b>Explosive Limits:</b>	LEL: N.D. UEL: N.D.
<b>Autoignition Pt:</b>	N.D.
<b>Suitable Extinguishing Media:</b>	Non-combustible liquid - use extinguishing media for underlying cause of fire.
<b>Unsuitable Extinguishing Media:</b>	None known.
<b>Fire Fighting Instructions:</b>	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
<b>Flammable Properties and Hazards:</b>	Flashpoint: No flash to boiling. This material does not exhibit a flashpoint per the Setaflash Closed Cup test method.
<b>Hazardous Combustion Products:</b>	Material will burn when dried. carbon monoxide, carbon dioxide

# SAFETY DATA SHEET

## Jasco Green Safer Paint Thinner for CARB

Revision: 10/02/2019

Supersedes Revision: 09/16/2019

### 6. ACCIDENTAL RELEASE MEASURES

**Steps To Be Taken In Case Material Is Released Or Spilled:** Isolate the immediate area. Prevent unauthorized entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to compatible containers. For large spills, dike ahead of the spill.

### 7. HANDLING AND STORAGE

**Precautions To Be Taken in Handling:** Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Avoid breathing of vapors or mist. Avoid contact with eyes and skin.

A source of clean water should be available in or near the work area for flushing of the eyes and skin if contact occurs.

**Precautions To Be Taken in Storing:** Keep container tightly closed when not in use. Store in a cool, dry place.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	ACGIH TLV	TLV: 200 mg/m <sup>3</sup>	
<b>Respiratory Equipment (Specify Type):</b>	When used as directed, respiratory equipment should not be needed.			
	Wear NIOSH approved respiratory protective equipment when vapor or mists may exceed applicable concentration limits.			
<b>Eye Protection:</b>	Safety glasses should be worn during normal handling of this material.			
	Where contact with the eyes or face is likely, a faceshield or chemical splash goggles should be worn to prevent eye contact.			
<b>Protective Gloves:</b>	Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.			
<b>Other Protective Clothing:</b>	Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.			
<b>Engineering Controls (Ventilation etc.):</b>	Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.			
	Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.			

## Jasco Green Safer Paint Thinner for CARB

Revision: 10/02/2019

Supersedes Revision: 09/16/2019

**Work/Hygienic/Maintenance Practices:** Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom.

Do not eat, drink, or smoke in the work area.

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical States:** [ ] Gas [X] Liquid [ ] Solid

**Appearance and Odor:** Milky Liquid

**pH:** N.D.

**Melting Point:** N.D.

**Boiling Point:** N.D.

**Flash Pt:** N.D.

**Evaporation Rate:** N.D.

**Flammability (solid, gas):** Non Combustible.

**Explosive Limits:** LEL: N.D. UEL: N.D.

**Vapor Pressure (vs. Air or mm Hg):** 17.2 MM HG at 68.0 F

**Vapor Density (vs. Air = 1):** N.D.

**Specific Gravity (Water = 1):** 0.915

**Density:** 7.61 LB/GL

**Solubility in Water:** Complete

**Octanol/Water Partition Coefficient:** ND

**VOC / Volume:** 0.0000 % WT

**Autoignition Pt:** N.D.

**Decomposition Temperature:** N.D.

**Viscosity:** N.D.

**Heat Value:** ND

**Additional Physical Information** ND = Not Determined

## 10. STABILITY AND REACTIVITY

**Stability:** Unstable [ ] Stable [X]

**Conditions To Avoid - Instability:** No data available.

**Incompatibility - Materials To Avoid:** Oxidizers

**Hazardous Decomposition or Byproducts:** carbon monoxide, carbon dioxide

**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [X]

## Jasco Green Safer Paint Thinner for CARB

Revision: 10/02/2019

Supersedes Revision: 09/16/2019

**Conditions To Avoid -** No data available.**Hazardous Reactions:****11. TOXICOLOGICAL INFORMATION****Toxicological Information:** This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.**Carcinogenicity/Other Information:** ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	n.a.	n.a.	A4	n.a.

**12. ECOLOGICAL INFORMATION****General Ecological Information:** This product has not been tested as a whole.**13. DISPOSAL CONSIDERATIONS****Waste Disposal Method:** Dispose in accordance with applicable local, state and federal regulations.**14. TRANSPORT INFORMATION****LAND TRANSPORT (US DOT):****DOT Proper Shipping Name:** Not Regulated.**DOT Hazard Class:****UN/NA Number:****Additional Transport Information:****15. REGULATORY INFORMATION****EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	TSCA: Inventory

**Additional Regulatory Information** This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

## Jasco Green Safer Paint Thinner for CARB

Revision: 10/02/2019

Supersedes Revision: 09/16/2019

**16. OTHER INFORMATION**

**Revision Date:** 10/02/2019  
**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Additional Information About This Product:** No data available.

**This Product:****Company Policy or****Disclaimer:**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.