	This SDS complies with the Canadian Hazardous I	Products Regulations of 2015.
1.	PRODUCT AND COMPANY	IDENTIFICATION
Product Name: Reference #: Company Name:	Klean-Strip Boiled Linseed Oil 1660C W. M. Barr 2105 Channel Avenue Memphis, TN 38113	
Web site address: Emergency Contact:	www.wmbarr.com 3E 24 Hour Emergency Contact	(800)451-8346
Information: Intended Use: Product Code:	W.M. Barr Customer Service Paint Thinner GLO45, QLO45, CLO45, GKLO145, Q	(800)398-3892 KLO146
	2. HAZARDS IDENTIF	ICATION
GHS Signal Word: GHS Hazard Phrases: GHS Precautionary Phrases GHS Response Phrases: GHS Storage and Disposal Phrases:	None s:	
OSHA Regulatory Status: Medical Conditions Genera Aggravated By Exposure:		
3. CC	OMPOSITION/INFORMATION	N ON INGREDIENTS
	nponents (Chemical Name) Concentra   alt manganese salt {Linseed oil, cobalt driers} 80.0 -100.0	
	4. FIRST AID MEAS	SURES
Emergency and First Aid Procedures:	INHALATION:	move to fresh air. If not breathing, give artificial
	SKIN CONTACT: wash with soap and water.	
	EYE CONTACT: Flush eye with water for at least 15 mir	nutes. Get immediate medical attention.
	INGESTION: Call your poison control center, hospita instructions.	al emergency room, or physician immediately for
Signs and Symptoms Of Exposure:	See Potential Health Effects.	

	5. FIRE F	IGHTING MEASURES			
Flammability Classification:	IIIB				
Flash Pt:	98.9 C (210.00 F)				
Explosive Limits:	LEL:	UEL:			
Autoignition Pt:	> 343.9 C (> 651.00	) F)			
Suitable Extinguishing Media	a:Use carbon dioxide,	, dry powder, or foam.			
Fire Fighting Instructions:	buildings or confined	iratory protection should be provided for fire figh d areas. Storage containers exposed to fire sho ent pressure build-up. Stay away from heads of ense heat or flame.	uld be kept cool with		
Flammable Properties and Hazards:	RISK OF FIRE FROM SPONTANEOUS COMBUSTION EXISTS WITH THIS PRODUCT.				
	handled properly. In Spread out all oily m airy spot for 24 hour with water and deter clothes, tools, rags,	d other oily materials can cause spontaneous c mmediately after use, and before disposal or sto naterials outside to dry by flattening them out to rs at temperatures above 40 degrees F, or (2) W rgent and rinse. Repeat until you have removed paper, clothing, mops, and any other materials accidental spill. Make certain all wash and rinse	orage, you MUST (1) their full size in an /ash them thoroughly d all oil from all contacted during use		
Hazardous Combustion	Carbon monoxide a	nd carbon dioxide.			
Products:					
	6. ACCIDENT	AL RELEASE MEASURES			
Steps To Be Taken In Case Material Is Released Or Spilled:	of low areas, and ve	y people away; isolate hazard area and deny en entilate closed spaces before entering. Shut of lames out of hazard area.			
	•	up liquid with sand, earth or other noncombustib tic container where applicable.	le absorbent material		
	Large Spills: dike f	ar ahead of spill for later disposal.			
	7. HAND	LING AND STORAGE			
Precautions To Be Taken in Handling:	container retains res	autions and directions on product label before us sidue, follow all label warnings even after contai ontainer according to all regulations. Do not reu	ner is empty.		
Precautions To Be Taken in Storing:		tly closed when not in use. Store in a cool, dry pevated temperatures.	blace. Do not store		
8. EXP	OSURE CONT	ROLS/PERSONAL PROTECTIO	N		
CAS # Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations		
68553-15-1 Linseed oil, cobalt manganese salt {Linseed oil, manganese and cobalt driers}	ACGIH TLV	TWA: 0.02 mg/m3 (resp.) 0.1 mg/m3 (IHL)			
5					

CEIL: 5 mg/m3

Licensed to W.M. Barr and Company: MIRS SDS, (c) A V Systems, Inc.

**Recommended Exposure** 

OSHA PELs

vegetable oil mist

Г

## **SAFETY DATA SHEET** Klean-Strip Boiled Linseed Oil

	Supersedes Revision: 0//21/2020			
Limits:	ACGIH: TLV: 10 mg/m3 OSHA PEL - TWA: 15 mg/m3, TWA: 5 mg/m3			
Respiratory Equipment (Specify Type):	For occasional consumer use - Use with adequate ventilation to prevent a build-up of vapors in confined areas. Open windows or position fans to provide cross ventilation. If a mild to strong odor is noticeable, ventilation is not adequate.			
	For OSHA controlled workplace and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLVs.			
	For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirators. A dust mask does not provide protection against vapors.			
Eye Protection:	Safety glasses, chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.			
Protective Gloves:	Wear impermeable gloves. Gloves contaminated with product should be discarded. Follow disposal procedures as described in Section 5 and Section 7.			
Other Protective Clothing:	Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.			
Engineering Controls (Ventilation etc.):	Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering STOP ventilation is inadequate. Leave area immediately and move to fresh air.			
Work/Hygienic/Maintenance Practices:	A source of clean water should be available in the work area for flushing of eyes and skin.			
	Clothing that becomes soiled with product should be removed as soon as possible and laundered separately. Follow procedures outlined in Section 7, Handling and Storage.			
	Wash hands thoroughly after use and before eating, drinking, or smoking.			
9.	PHYSICAL AND CHEMICAL PROPERTIES			
Physical States: Appearance and Odor: pH: Melting Point:	[ ] Gas [X ] Liquid [ ] Solid Clear Amber			
Boiling Point: Flash Pt: Evaporation Rate:	98.9 C (210.00 F)			
Flammability (solid, gas): Explosive Limits:	LEL: UEL:			
Vapor Pressure (vs. Air or mm Hg):				
Vapor Density (vs. Air = 1): Specific Gravity (Water =	0.93 at 25.0 C ( 77.0 F)			
1): Licensed to W.M. Barr and Company:	MIRS SDS, (c) A V Systems, Inc. Multi-region format			

Solubility in V Saturated Vap Concentration Octanol/Wate Coefficient: Autoignition F Decompositio Temperature: Viscosity:	oor 1: r Partition Pt:	> 343.9 C (> 651.0	) F)				
Information w primary physi	-						
		10. STABI	LITY AND RE	ACTIVIT	Y		
Stability: Conditions To Instability:			table [ X ]				
Avoid:	y - Materials To	Incompatible with s	trong oxidizing age	ents.			
	composition or	Decomposition may	/ produce carbon n	nonoxide and	carbon diox	ide.	
Possibility of Reactions: Conditions To		Will occur [ ]	Will not occur [ X ]				
Hazardous Re							
		11. TOXICO	LOGICAL INF	ORMATI	ON		
Toxicological	Information:	Refer to section 2 f CAS# 68553-15-1: Standard Draize Te Result: Sense Organs and cochlear structure of Nutritional and Gro - Cutaneous Toxicit York, Academic Pre	est, Skin, Human, 3 Special Senses (N or function. ss Metabolic:Weigh cy, Proceedings of	00.0 MG, 3 D lose, Eye, Ea ht loss or deci the 3rd Confe	r, and Taste) reased weigl erence, 1976	nt gain. , D, V.A., an	
CAS #		ponents (Chemical N	-	NTP	IARC	ACGIH	OSHA
68553-15-1	Linseed oil, cobal manganese and o	t manganese salt {Lin cobalt driers}	seed oil,				
		12. ECOLO	OGICAL INFO	RMATIO	N		
General Ecolo Information:	ogical	This product has no	ot been tested as a	whole.			

## **SAFETY DATA SHEET** Klean-Strip Boiled Linseed Oil

		13. DISPOSAL CO				
Waste Dispo	sal Method:	Dispose in accordance with a			gulations.	
		14. TRANSPOR	<b>F INFORMAT</b>	ION		
	SPORT (US DOT	):				
DOT Haza UN/NA Nu			R			
	ping Name:	Not Regulated by 49 CFF	र			
Hazard Cla	ass:		TDG Class	ification:		
		15. REGULATOR	Y INFORMA	TION		
EPA SARA (S	uperfund Amendn	nents and Reauthorization Act	of 1986) Lists			
CAS # 68553-15-1		ponents (Chemical Name) It manganese salt {Linseed oil, cobalt driers}	<b>S. 302 (EHS)</b> No	<b>S. 304 RQ</b> No	<b>S. 313 (TRI)</b> Yes-Cat. N096, N450	
CAS #	Hazardous Com	ponents (Chemical Name)	Canadian NPRI	Canadian Toxic	Canadian DSL	
68553-15-1	Linseed oil, coba manganese and	lt manganese salt  {Linseed oil, cobalt driers}	Yes - Cat.			
CAS #	Hazardous Com	ponents (Chemical Name)	Other US EPA or State Lists			
68553-15-1	Linseed oil, coba manganese and	It manganese salt {Linseed oil, cobalt driers}	il, CAA HAP,ODC: Yes - Cat. TSCA: Inventory			
Additional Re	egulatory	This product is regulated by and is subject to certain labe Act. These requirements diff required for safety data shee information, including direction using the product.	eling requirements fer from the classifi ets (SDS). The pro	under the Federal I cation criteria and I duct label also inclu	Hazardous Substance nazard information udes other important	
		16. OTHER IN	IFORMATIO	N		
Revision Dat Preparer Nan	-	01/11/2023 W.M. Barr EHS Dept (901	<b>Previous re</b> )775-0100	vision:	07/21/2020	
Additional In This Product	formation About	t				
Company Policy or Disclaimer:		The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.				