Printed: 01/12/2022 Revision: 01/12/2022

Page: 1 of 8

Supersedes Revision: 01/06/2022

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Code:** KWS4500KS

**Product Name:** KLEAN STRIP SPRAYABLE STRIPPER

W. M. Barr **Company Name: Phone Number:** (901)775-0100

2105 Channel Avenue

Memphis, TN 38113

www.wmbarr.com Web site address:

3E 24 Hour Emergency Contact **Emergency Contact:** (800)451-8346

Information: W.M. Barr Customer Service (800)398-3892

Intended Use: Paint/Varnish Remover

Product Code: GKSS250, GKSS250BLK, QKSS251, QKSS251BLK

### 2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2

Acute Toxicity: Inhalation, Category 4 Acute Toxicity: Oral, Category 4 Skin Corrosion/Irritation, Category 2

Serious Eye Damage/Eye Irritation, Category 2

Specific Target Organ Toxicity (repeated exposure), Category 2







**GHS Signal Word:** Danger

**GHS Hazard Phrases:** Highly flammable liquid and vapor.

Harmfull if swallowed or if inhaled.

Causes skin irritation. Causes serious eye irritation.

Harmful if inhaled.

May cause damage to {organs} through prolonged or repeated exposure.

GHS Precautionary Phrases: Keep away from {heat/sparks/open flames/hot surfaces}. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment. Do not breathe {dust/fume/gas/mist/vapors/spray}.

Wash {hands} thoroughly after handling.

Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Wear {protective gloves/protective clothing/eye protection/face protection}.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. **GHS Response Phrases:** 

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin

with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention/advice if you feel unwell. Specific treatment {see ... on this label}.

Rinse mouth.

If skin irritation occurs, get medical advice/attention.

Licensed to W.M. Barr and Company: MIRS MSDS, (c) A V Systems, Inc.

**GHS** format

Page: 2 of 8 Printed: 01/12/2022

Revision: 01/12/2022

Supersedes Revision: 01/06/2022

If eye irritation persists, get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire, use {...} to extinguish.

**GHS Storage and Disposal** 

Phrases:

Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status: This material is classification

Potential Health Effects (Acute and Chronic):

This material is classified as hazardous under OSHA regulations.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration
616-38-6	Dimethyl carbonate	30.0 -60.0 %
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	10.0 -30.0 %
67-68-5	Methyl sulfoxide {Dimethyl sulfoxide; DMSO}	10.0 -30.0 %
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	3.0 -7.0 %
1095-66-5	Oleic acid, compound with morpholine (1:1)	1.0 -5.0 %
68439-46-3	Alcohols, C9-11, ethoxylated	0.1 -1.0 %
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	0.1 -1.0 %
110-91-8	Morpholine {Diethylene imidoxide}	0.1 -1.0 %
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	0.1 -1.0 %

Additional Chemical

Information

Specific percentage of composition is being withheld as a trade secret.

#### 4. FIRST AID MEASURES

# Emergency and First Aid

Procedures:

Skin:

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

Signs and Symptoms Of

Exposure:

Note to Physician:

See Section 2.

Page: 3 of 8 Printed: 01/12/2022 Revision: 01/12/2022

Supersedes Revision: 01/06/2022

#### 5. FIRE FIGHTING MEASURES

Flammable Classification 1B

72.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash) Flash Pt:

**Explosive Limits:** LEL: UEL:

**Autoignition Pt:** N.D.

Suitable Extinguishing Media: Use carbon dioxide, dry powder, or alcohol resistant foam.

Unsuitable Extinguishing

Do not use straight streams of water. If water is used, use a water spray or fog.

Media:

Self-contained respiratory protection should be provided for fire fighters fighting fires in Fire Fighting Instructions:

> buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have

been exposed to intense heat or flame.

Flammable Properties and

Hazards:

Danger! Flammable. Keep away from heat, sparks, flame, and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by synthetic clothing and

other sources.

**Hazardous Combustion** 

**Products:** 

Carbon monoxide, carbon dioxide. sulfur oxides, hydrogen sulfide

#### 6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:

Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

## 7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Licensed to W.M. Barr and Company: MIRS MSDS, (c) A V Systems, Inc.

**GHS** format

Page: 4 of 8 Printed: 01/12/2022 Revision: 01/12/2022

Supersedes Revision: 01/06/2022

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

Precautions To Be Taken in Storing:

Store in a cool place in original container and protect from sunlight. Exposure to high temperatures or prolonged exposure to sun may cause can to leak or swell. Do not store near flames or at elevated temperatures.

Keep container tightly closed when not in use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS#	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
616-38-6	Dimethyl carbonate	ACGIH TLV	TLV: 500 ppm STEL: 750 ppm	
		OSHA PELs	PEL: 1000 ppm	
1330-20-7 {Benzene,	Xylene (mixed isomers) dimethyl-}	ACGIH TLV	TLV: 100 ppm STEL: 150 ppm	
		OSHA PELs	PEL: 100 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	
100-41-4 {Ethylbenz	Ethylbenzene zol; Phenylethane}	ACGIH TLV	TLV: 20 ppm STEL: 125 ppm	
		OSHA PELs	PEL: 100 ppm	
98-82-8 1-Methyle	Cumene {Benzene, thyl-; Isopropylbenzene}	ACGIH TLV	TLV: 50 ppm	
		OSHA PELs	PEL: 50 ppm	
110-91-8 imidoxide}	Morpholine (Diethylene	ACGIH TLV	TLV: 20 ppm	
		OSHA PELs	PEL: 20 ppm	
67-56-1 Carbinol;	Methanol {Methyl alcohol; Wood alcohol}	ACGIH TLV	TLV: 200 ppm STEL: 250 ppm	
		OSHA PELs	PEL: 200 ppm	

# Respiratory Equipment (Specify Type):

For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved self-contained breathing apparatus or powered air

supply respirator or loose fitting hood.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

**Eye Protection:** Chemical goggles, or face shields are recommended to safeguard against potential eye

contact, irritation, or injury. Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to

help reduce chemical contact to the face and eyes.

**Protective Gloves:** Wear gloves with as much resistance to the chemical ingredients as possible. Laminate

film gloves offer the best protection. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

Other Protective Clothing: Various application methods can dictate use of additional protective safety equipment,

such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly

Licensed to W.M. Barr and Company: MIRS MSDS, (c) A V Systems, Inc.

Printed: 01/12/2022 Revision: 01/12/2022

Page: 5 of 8

Supersedes Revision: 01/06/2022

clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

Engineering Controls (Ventilation etc.):

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. If the work area is not well ventilated, DO NOT use this product. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas.

Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to

Work/Hygienic/Maintenance

Wash hands thoroughly after use and before eating, drinking, or smoking.

Practices:

Do not eat, drink, or smoke in the work area.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [ ] Gas [ X ] Liquid [ ] Solid

Appearance and Odor: Opaque viscous, aromatic odor

Odor threshold not determined.

pH: N.D.

**Melting Point:** - N.D. **Boiling Point:** > 99.90 F

Flash Pt: 72.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

**Evaporation Rate:** < 1 (BuAC=1)

Flammability (solid, gas):

Explosive Limits: LEL: UEL:

N.D.

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): N.D.

Specific Gravity (Water = 1): 0.992 - 1.015

Density: 8.25 - 8.45 LB/GL

Solubility in Water: Appreciable

Solubility Notes:

Printed: 01/12/2022 Revision: 01/12/2022

Page: 6 of 8

Supersedes Revision: 01/06/2022

Octanol/Water Partition

Coefficient:

Percent Volatile: 95.1 % by weight. VOC / Volume: 50.0000 % WT

**Autoignition Pt:** N.D.

**Decomposition Temperature:** 

800 - 2800 CPS Viscosity: Additional Physical ND = not determined.

Information

## 10. STABILITY AND REACTIVITY

Stability: Unstable [ ] Stable [X]

**Conditions To Avoid -**

Instability:

Stable

ND

Incompatibility - Materials To Bases, oxygen, sodium, potassium, strong oxidizers, reactive metals, strong acids

Avoid:

Hazardous Decomposition or Carbon monoxide, carbon dioxide

Byproducts:

Possibility of Hazardous

Will occur [ ] Will not occur [ X ]

Reactions:

**Conditions To Avoid -**Will not occur.

Hazardous Reactions:

#### 11. TOXICOLOGICAL INFORMATION

This product has not been tested as a whole. Refer to section 2 for acute and chronic Toxicological Information:

effects.

CAS# 1330-20-7:

Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H.

Result:

Behavioral: Muscle contraction or spasticity. Lungs, Thorax, or Respiration:Other changes.

- Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ.,

Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974

Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe.

Result:

Behavioral: General anesthetic.

Behavioral: Somnolence (general depressed activity).

Behavioral: Irritability.

- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku,", Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho,

Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

CAS# 100-41-4:

Tumorigenic Effects:, TCLo, Inhalation, Rat, 750.0 ppm.

Tumorigenic: Carcinogenic by RTECS criteria.

Kidney, Ureter, Bladder: Tumors.

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe.

Licensed to W.M. Barr and Company: MIRS MSDS, (c) A V Systems, Inc. **GHS** format

Page: 7 of 8 Printed: 01/12/2022

Revision: 01/12/2022 Supersedes Revision: 01/06/2022

Result:

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).

Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth). Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave.,

Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 68439-46-3:

Acute toxicity, LD50, Oral, Rat, 1378. MG/KG.

Result:

Behavioral: Somnolence (general depressed activity).

Behavioral: Ataxia.

Gastrointestinal: Hypermotility, diarrhea.

- Journal of the American College of Toxicology., Mary Ann Liebert, Inc., New York, NY,

Vol/p/yr: 10(4),427, 1991

**Chronic Toxicological** 

Effects:

This product has not been tested as a whole.

Carcinogenicity/Other

IARC 2B - Possibly Carcinogenic to Humans

Information: IARC 3: Not Classifiable as to Carcinogenicity in Humans

ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans ACGIH

A4 - Not Classifiable as a Human Carcinogen.

CAS # Hazardous Components (Chemical Name)		NTP	IARC	ACGIH	OSHA
616-38-6	Dimethyl carbonate				
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	3	A4		
67-68-5	Methyl sulfoxide {Dimethyl sulfoxide; DMSO}				
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}		2B	A3	
1095-66-5	Oleic acid, compound with morpholine (1:1)				
68439-46-3	Alcohols, C9-11, ethoxylated				
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	Possible	2B		
110-91-8	Morpholine {Diethylene imidoxide}		3	A4	
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}				

#### 12. ECOLOGICAL INFORMATION

General Ecological This product has n

Information:

This product has not been tested as a whole.

#### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with all applicable local, state, and federal regulations.

#### 14. TRANSPORT INFORMATION

Page: 8 of 8 Printed: 01/12/2022 Revision: 01/12/2022

Supersedes Revision: 01/06/2022

LAND TRANSPORT (US DOT):

Paint related material **DOT Proper Shipping Name:** 

**DOT Hazard Class:** FLAMMABLE LIQUID

UN1263 **UN/NA Number: Packing Group:** Ш

LAND TRANSPORT (Canadian TDG):

**TDG Shipping Name:** 

Ш **UN Number:** 1263 **Packing Group:** 

**Hazard Class:** 3 - FLAMMABLE LIQUID TDG Classification:

Additional Transport

The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, Information:

> or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

## 15. REGULATORY INFORMATION

**Additional Regulatory** Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

#### **16. OTHER INFORMATION**

01/12/2022 Previous revision: 01/06/2022 **Revision Date:** 

**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Additional Information About** 

This Product:

**Company Policy or** 

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

Licensed to W.M. Barr and Company: MIRS MSDS, (c) A V Systems, Inc.

**GHS** format