Revision: 10/03/2019

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Jasco Brush Cleaner

Company Name: W. M. Barr Phone Number:

2105 Channel Avenue (901)775-0100

Memphis, TN 38113

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346

**Information:** W.M. Barr Customer Service (800)398-3892

**Intended Use:** Clean up of natural and synthetic paint brushes.

Product Code: QJBC250CA, GJBC220CA

## 2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2

Serious Eye Damage/Eye Irritation, Category 2

Specific Target Organ Toxicity (single exposure), Category 3

**Aspiration Toxicity, Category 2** 







GHS Signal Word: Danger

GHS Hazard Phrases: Highly flammable liquid and vapor.

May be harmful if swallowed and enters airways.

Causes serious eye irritation.

May cause drowsiness or dizziness.

GHS Precautionary Phrases: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing gas/mist/vapors/spray.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Keep cool.

GHS Response Phrases: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin

with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Do NOT induce vomiting.

If eye irritation persists, get medical advice/attention. In case of fire, use dry chemical powder to extinguish. Store container tightly closed in well-ventilated place.

GHS Storage and Disposal

Phrases: Store locked up.

Dispose of contents/container according to local, state and federal regulations.

Licensed to W.M. Barr and Company

**GHS** format

Page: 2 of 7

# SAFETY DATA SHEET Jasco Brush Cleaner

Revision: 10/03/2019

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

Inhalation Exposure Effects:

Vapor harmful. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and loss of consciousness and even death). High vapor concentrations are irritating to the eyes, nose, throat, and

Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

Skin Contact Exposure Effects:

Moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Eye Contact Exposure Effects:

Contact with the eye may cause moderate to severe irritation.

Ingestion Acute Exposure Effects:

Product may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. May produce central nervous system effects, which may include dizziness, loss of balance and coordination, unconsciousness, coma and even death.

Target Organs: Central Nervous System, Respiratory System, Eye, Skin

Primary Routes of Entry: Inhalation, Ingestion

**Medical Conditions Generally** Diseases of the skin, eyes, and lung (asthma-like conditions). **Aggravated By Exposure:** 

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration	
67-64-1	Acetone {2-Propanone}	80.0 -100.0 %	
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester}	1.0 -5.0 %	

Additional Chemical

Specific percentage of composition is being withheld as a trade secret.

nformation

Revision: 10/03/2019

### 4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

Inhalation:

If user experiences breathing difficulty, move to air free of vapors, Administer oxygen or

artificial medical assistance can be rendered.

Skin Contact:

Wash with soap and large quantities of water and seek medical attention if irritation from

contact persists.

Eye Contact:

Flush with large quantities of water for at least 15 minutes and seek immediate medical

attention.

Ingestion:

Do not induce vomiting. Call your local poison control center, hospital emergency room

or physician immediately for instructions to induce vomiting.

Signs and Symptoms Of

**Exposure:** 

See Potential Health Effects.

## 5. FIRE FIGHTING MEASURES

NFPA Class IB

Flash Pt: 0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

**Explosive Limits:** LEL: 1.7 % UEL: 13 %

Autoignition Pt: N.D.

Suitable Extinguishing Media:Use carbon dioxide, dry powder, water spray, or alcohol resistant foam.

Unsuitable Extinguishing

Media:

None known.

**Fire Fighting Instructions:** Self-contained respiratory protection should be provided for fire fighters fighting fires in

buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have

been exposed to intense heat or flame.

Flammable Properties and

Hazards:

Extremely flammable. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by an ignition source, such as pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at location distant from the material handling point. Product residue can ignite

explosively. Do not weld or cut on empty containers.

**Hazardous Combustion** 

Products:

Carbon monoxide and carbon dioxide, other various unburned hydrocarbons.

## 6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and

Revision: 10/03/2019

place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal

regulations.

Keep out of drains, sewers, and bodies of water.

### 7. HANDLING AND STORAGE

# Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Precautions To Be Taken in Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS#	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
67-64-1	Acetone {2-Propanone}	ACGIH TLV	TLV: 500 ppm STEL: 750 ppm	
		OSHA PELs	PEL: 1000 ppm	
123-86-4 acetate. /	Butyl acetate {n-Butyl Acetic acid, Butyl ester}	ACGIH TLV	TLV: 150 ppm STEL: 200 ppm	
		OSHA PELs	PEL: 150 ppm	

# Respiratory Equipment (Specify Type):

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV.

For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

**Eye Protection:** Safety glasses, goggles or face shields are recommended to safeguard against potential

eye contact, irritation, or injury.

**Protective Gloves:** Wear gloves with as much resistance to the chemical ingredients as possible. Glove

materials such as natural rubber and neoprene may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be

discarded and not reused.

Other Protective Clothing: Various application methods can dictate use of additional protective safety equipment,

such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.):

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - Stop - ventilation is inadequate. Leave area immediately.

Revision: 10/03/2019

Work/Hygienic/Maintenance Wash hands thoroughly after use and before eating, drinking, or smoking.

Practices:

Do not eat, drink, or smoke in the work area.

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency

eyewash and safety shower.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

[ ] Solid **Physical States:** [ ] Gas [X] Liquid

Water White / Free and Clear Appearance and Odor:

Odor threshold not determined.

N.D. pH: Melting Point: N.D. 131.00 F **Boiling Point:** 

Flash Pt: 0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

> 1 Evaporation Rate:

NFPA Class IB Flammability (solid, gas):

LEL: 1.7 % UEL: 13 % **Explosive Limits:** N.D.

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): > 1 Specific Gravity (Water = 1): 0.792

Density: 6.592 LB/GL Solubility in Water: Complete

Octanol/Water Partition ND

Coefficient:

Percent Volatile: 100.0 % by weight. 3.0000 % WT VOC / Volume:

**Autoignition Pt:** N.D. **Decomposition Temperature:** N.D. Viscosity: N.D.

Additional Physical ND = Not Determined

Information

## **10. STABILITY AND REACTIVITY**

Unstable [ ] Stable [X] Stability:

Conditions To Avoid -No data available.

Instability:

Incompatibility - Materials To Strong oxidizing agents.

Avoid:

2-Propanone may form explosive mixtures with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide,

and thioglycol.

Hazardous Decomposition or Decomposition may produce carbon monoxide, carbon dioxide, and unidentified organic

Byproducts: compounds in black smoke.

Possibility of Hazardous Will occur [ ] Will not occur [ X ]

Reactions:

No data available. **Conditions To Avoid -**

Licensed to W.M. Barr and Company

**GHS** format

Revision: 10/03/2019

**Hazardous Reactions:** 

## 11. TOXICOLOGICAL INFORMATION

**Toxicological Information:** This product has not been tested as a whole. Refer to section 2 for acute and chronic

effects.

CAS# 67-64-1:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Change in motor activity (specific assay). Behavioral: Alteration of classical conditioning.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave.,

Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester}	n.a.	n.a.	n.a.	n.a.

### 12. ECOLOGICAL INFORMATION

General Ecological

No information available for this product as a whole.

Information:

### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with all applicable local, state, and federal regulations.

Keep out of sewers and bodies of water.

### 14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Paint Related Material

**DOT Hazard Class:** 3 FLAMMABLE LIQUID

UN/NA Number: UN1263 Packing Group: II



**Additional Transport** 

Information:

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### 15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone {2-Propanone}	No	Yes NA	No
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester}	No	Yes NA	No

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

67-64-1 Acetone {2-Propanone} TSCA: Inventory

123-86-4 Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester} CWA NPDES

TSCA: Inventory

Page: 7 of 7

# SAFETY DATA SHEET Jasco Brush Cleaner

Revision: 10/03/2019

**Regulatory Information:** 

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

# **16. OTHER INFORMATION**

**Revision Date:** 10/03/2019

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About No data available.

This Product: